

LED

## TRACK SPOTLIGHT



## ILYAD W

Datasheet EN n°17B

Interior Spot mounted on a 3-circuit adapter.  
 Projector equipped with a high power LED.  
 Asymmetric distribution for highly uniform wallwashing.  
 Equipped with a single dimmer.  
 Comes with a 3-circuit adapter.  
 Tilt 146 °. Azimuth 360°.  
 Ability to integrate a Lee filter and shutters (accessories).


Warranty: 3 years\*



## Technical characteristics

Light source	LED
Led Power/ Power consumption	18 W / 21W
Opening Angle	20° / 35° / 48° / 90°
Color Temperature	Warm white – Neutral White
Led luminous Flux	1990 - 2050 lm**
CRI	97 - R9>90
Maintaining Flux L80B10	95 000 hours
Dimming / Control	Integrated potentiometer
Cooling	Passive
Materials used	Body : Aluminium – Painted steel
Finish	Black - White
Weight	1,200 kg

\*\* International standards set the tolerance of the initial flux and the load associated with it at +/-10%.  
 The color temperature is subject to a tolerance of up to +/- 150 Kelvin compared to the nominal value. Unless otherwise indicated, values are applicable for an ambient temperature of 25 °.



Dimensions en mm

\* See our warranty conditions at [www.spx-lighting.com](http://www.spx-lighting.com)  
 The only contractual forms are those available on the site at the time of the order.

1

[www.spx-lighting.com](http://www.spx-lighting.com)

All rights reserved. Reproduction in whole or in part is prohibited, without prior written permission of SPX. Information contained in this document does not contractually bound SPX. Despite the care that SPX has brought to the accuracy and precision of this information, the responsibility for SPX cannot be sought in case of inaccurate information. SPX reserves the right to change this information at any time without prior notice. No liability is accepted by SPX for the consequences of the use of this document. This publication does not imply any transfer of intellectual property rights.

## TRACK SPOTLIGHT

## ILYAD W

Datasheet EN n°17B

## Product reference

Power consumption	Mounting	Beam Angle	Color Temperature	Black	White
21W	3 Circuit track	Asymmetric	Warm white	Réf : PRI00725	Réf : PRI00726
			Neutral White	Réf : PRI00727	Réf : PRI00728

\* See our warranty conditions at [www.spx-lighting.com](http://www.spx-lighting.com)  
 The only contractual forms are those available on the site at the time of the order.

2

**[www.spx-lighting.com](http://www.spx-lighting.com)**

All rights reserved. Reproduction in whole or in part is prohibited, without prior written permission of SPX. Information contained in this document does not contractually bound SPX. Despite the care that SPX has brought to the accuracy and precision of this information, the responsibility for SPX cannot be sought in case of inaccurate information. SPX reserves the right to change this information at any time without prior notice. No liability is accepted by SPX for the consequences of the use of this document. This publication does not imply any transfer of intellectual property rights.

