





MOOVEO HR

Track or surface mounted mini spotlight, high performance, high Led output, focusable and on-board dimming.

Track mounted (1 circuit - 12V), surface mounted or Jack fitted.

Inclinaison +/- 135°.

Rotation: 350°.



Technical specifications

Led Power Rating Beam Angle Color temperature (Step Macadam SDCM2) Led nominal output CRI (Ra) Lumen maintenance L80B10 Dimming/control Thermal dissipation Housing materials

Light source type

Finish

Weight

CE CB NT CA

LED 2 W

 $7^{\circ} > 30^{\circ} - 17^{\circ} > 37^{\circ}$ 3 000 K - 4 000 K 180 lm - 180 lm 95 95 50 000 operating hours

Potentiometer

Passive

Aluminium - Optical lens: glass

0,120 kg (track adaptor) 0,150 kg (surface mounting)

0,150 kg (jack fitting)

Anodized aluminium - black finish upon request







Islamic tresures in africa, from Tumbuctu to Zanzibar exhibition Mohamed VI museum – Rabat - Morroco. Lighting design : GELATIC @Spx lighting





SPX Lighting - Offices: 10 rue des Marronniers 94 240 L'Hay Les Roses - France. Factory: Zac des Coinchettes - 36 100 Issoudun - France.

Contacts +33 01 82 33 02 80 - contact@spx-lighting.com - www.spx-lighting.com

All rights reserved. Partial or complete reproductions is prohibited unless written permission of SPX Lighting. Information contained in this document does not contractually bind SPX Lighting. Despite the care SPX Lighting brings to the accuracy and precision of the present information, the responsibility of SPX Lighting cannot not be sought in case of inaccurate informations. SPX Lighting reserves the right to change this information at any time without prior notice. SPX Lighting cannot be held labele for the consequences of the use of the present document. This publication does not imply any transfer of intellectual property rights. e of publication February 2023.




100VEO HR




Mounting versions


Circuit Track Adaptor 12V



Jack fitting



Surface mounting version delivered with a length of 1m of cable



Accessories

Track Accessories

Jack Accessories









Twin jack









Zoom 7° to 30°





Tray



Zoom 17° to 37°



VERSION 23A

SPX Lighting - Offices: 10 rue des Marronniers 94 240 L'Hay Les Roses - France.


Factory: Zac des Coinchettes - 36 100 Issoudun - France.

Contacts +33 01 82 33 02 80 - contact@spx-lighting.com - www.spx-lighting.com
All rights reserved. Partial or complete reproductions is prohibited unless writen permission of SPX Lighting. Information contained in this document does not contractually bind SPX Lighting. Despite the care SPX Lighting brings to the accuracy and precision of the present information, the responsibility of SPX Lighting cannot be held liable for the consequences of the use of the present document. This publication does not imply any transfer of intellectual property rights.



OVEO HR

Colorimetry Data





VERSION 23A

SPX Lighting - Offices: 10 rue des Marronniers 94 240 L'Hay Les Roses - France. Factory: Zac des Coinchettes - 36 100 Issoudun - France.


Contacts +33 01 82 33 02 80 - contact@spx-lighting.com - www.spx-lighting.com

All rights reserved. Partial or complete reproductions is prohibited unless written permission of SPX Lighting. Information contained in this document does not contractually bind SPX Lighting. Despite the care SPX Lighting brings to the accuracy and precision of the present information, the responsibility of SPX Lighting can not be sought in case of inaccurate information. SPX Lighting reserves the right to change this information at any time without prior notice. SPX Lighting cannot be held liable for the consequences of the use of the present document. This publication does not in prival part are responsibility of intellectual property rights.



OOVEO HR

Colorimetry Data





VERSION 23A

SPX Lighting - Offices: 10 rue des Marronniers 94 240 L'Hay Les Roses - France. Factory: Zac des Coinchettes - 36 100 Issoudun - France.


Contacts +33 01 82 33 02 80 - contact@spx-lighting.com - www.spx-lighting.com
All rights reserved. Partial or complete reproductions is prohibited unless written permission of SPX Lighting, Information contained in this document does not contractually bind to precision of the present information, the responsibility of SPX Lighting reserves the right to change this informat for the consequences of the use of the present document. This publication does not imply any transfer of intellectual property rights.




MOOVEO HR



Photometry Data














VERSION 23A




MOOVEO HR



Photometry Data







SPX Lighting - Offices: 10 rue des Marronniers 94 240 L'Hay Les Roses - France. Factory: Zac des Coinchettes - 36 100 Issoudun - France.

Contacts +33 01 82 33 02 80 - contact@spx-lighting.com - www.spx-lighting.com
All rights reserved. Partial or complete reproductions is prohibited unless written permission of SPX Lighting. Information at this document does not contractually bind SPX Lighting. Despite the care SPX Lighting brings to the accuracy and precision of the present information, the responsibility of SPX Lighting can not be sought in case of inaccurate information. SPX Lighting reserves the right to change this information at any time without prior notice. SPX Lighting cannot be held liable for the consequences of the use of the present document. This publication does not imply any transfer of intellectual property rights.

VERSION 234

VERSION 235



VERSION 23A



MOOVEO HR



Items References

Power consumption	Mounting versions	Beam angle	On board dimming	Power Consumption	Warm White	Neutral White	
3W	Circuit Track Adaptor 12V	7 > 30°	yes	12 V DC	PRI00532	PRI00533	**
3W	Circuit Track Adaptor 12V	17 > 37°	yes	12 V DC	PRI00535	PRI00536	**
3W	Surface Mounted	7 > 30°	yes	12 V DC	PRI00903	PRI00904	
3W	Surface Mounted	17 > 37°	yes	12 V DC	PRI00905	PRI00906	
3W	Jack	7 > 30°	yes	12 V DC	PRI00911	PRI00912	
3W	Jack	17 > 37°	yes	12 V DC	PRI00913	PRI00914	

^{**}Certifications : Please check the technical specifications

References Power supply


For 1 to 17 Mooveo - 12V	ALI00129
For 1 to 34 Mooveo - 12V	ALI00132

Maximum voltage drop: 3,5V (on the Mooveo's terminals)

Accessories References

Track Accessories

1m black track – 12V	ACC00086
2m black track – 12V	ACC00087
3m black track – 12V	ACC00088
End feed connector-12V	ACC00089
End cap (Fig 2)	GB 41 -2
Straight connector (electrical junction) (Fig 3)	GB 21 - 2
Adjustable corner connector (electrical junction) (Fig 4)	GB 24 - 2
Middle feed connector (Fig 5) - 12 V	ACC00193



Accessoires Jack

MOOVEO Jack Tray	ACC00320	
Twing Jack MOOVEO Black	ACC00406	



Optical Zoom from 7° to 30°	ACC00323
Optical Zoom from 17° to 37°	ACC00326





VERSION 23A

SPX Lighting - Offices: 10 rue des Marronniers 94 240 L'Hay Les Roses - France. Factory: Zac des Coinchettes - 36 100 Issoudun - France.

Contacts +33 01 82 33 02 80 - contact@spx-lighting.com - www.spx-lighting.com
All rights reserved. Partial or complete reproductions is prohibited unless written permission of SPX Lighting. Information contained in this document does not contractually bind precision of the present information, the responsibility of SPX Lighting can not be sought in case of inaccurate information. SPX Lighting reserves the right to change this inform to the consequences of the use of the present document. This publication does not imply any transfer of intellectual property rights.

