#### **SYCLOSPOT Range**



### SYCLOSPOT LP35

High lumen output and low energy consumption spotlight. Fixed commutable optical lenses, beam angle 22° or 40°. 230 Volts direct power supply.

Several mounting possibilities: 3 circuits track adaptor, hook mounting, wall mounting or tieback mounting.

Other mounting options on demand.

Tilt angle 200° - azimuth 365°.

Holding positions by friction and locking screw. Handle

Integrated magnetic filter holder.

Optional barn-doors.





### Technical specifications

Light source type Led Power Rating Beam angle

Color temperature (Step Macadam SDMC2)


Led nominal output

CRI (Ra) R9

Lumen maintenance L80B10

Dimming/control

Weight Finish

















LED 35W

22° or 40°

3 000 K - 4 000 K 3 096 lm - 3 175 lm 97 97

> 96

90 000 operating hours

Potentiometer / Phase cut / DALI 2 Casambi / Casambi + Potentiometer

**Passive** 

Body: anodized aluminium -

painted steel 1,610 Kg

Black or White - Other RAL colors

upon request







Thomas Henry Museum - Cherbourg- France @SPX LIGHTING











SPX Lighting - 10 rue des Marronniers 94 240 L'Hay Les Roses - France. Factory : Zac des Coinchettes - 36 100 Issoudun - France.

Contacts +33 01 82 33 02 80 - contact@spx-lighting.com - www.spx-lighting.com

All rights reserved. Partial or complete reproductions is prohibited unless written permission of SPX Lighting. Information contained in this document does not contractually bind SPX Lighting. Despite the care SPX Lighting brings to the accuracy and precision of the present information, the responsibility of SPX Lighting can not be sought in case of inaccurate information. SPX Lighting reserves the right to change this information at any time without prior notice. SPX Lighting cannot be held liable Date of publication February 2023.









### **Mounting versions**


#### 3 Circuits Track Adaptor




#### Tieback



#### Hook



#### Wall




#### **Accessories**




22° Optical lens with filter holder



40° Optical lens with filter holder



Adjustable hinged barn-doors (adaptable to the 22° or 40° optical lens)




Optical Zoom  $18^{\circ} < 42^{\circ}$  - with shutters







### **Colorimetry Data**






SPX Lighting - 10 rue des Marronniers 94 240 L'Hay Les Roses - France. Factory : Zac des Coinchettes - 36 100 Issoudun - France.







### **Colorimetry Data**













### **Photometry Data**



SYCLOSPOT LP35 3000K 22°




SYCLOSPOT LP35 3000K 40°






### **Photometry Data**



SYCLOSPOT LP35 4000K 22°



SYCLOSPOT LP35 4000K 40°



### **Items References**

Beam angle 22°

Power Consumption	Voltage	Mounting Versions	Dimming / Control	Beam Angle	Color Temperature	Black Finish	White Finish
40W	230Vac	3 Circuits Track Adaptor Nordic	Potentiometer	22°	Warm White	PRI01518	PRI01519
40W	230Vac	3 Circuits Track Adaptor Nordic	Potentiometer	22°	Neutral White	PRI01520	PRI01521
40W	230Vac	3 Circuits Track Adaptor Nordic DALI	DALI	22°	Warm White	PRI01522	PRI01523
40W	230Vac	3 Circuits Track Adaptor Nordic DALI	DALI	22°	Neutral White	PRI01524	PRI01525
40W	230Vac	3 Circuits Track Adaptor Nordic	PHASE	22°	Warm White	PRI01526	PRI01527
40W	230Vac	3 Circuits Track Adaptor Nordic	PHASE	22°	Neutral White	PRI01528	PRI01529
40W	230Vac	3 Circuits Track Adaptor Nordic	CASAMBI	22°	Warm White	PRI01530	PRI01531
40W	230Vac	3 Circuits Track Adaptor Nordic	CASAMBI	22°	Neutral White	PRI01532	PRI01533
40W	230Vac	3 Circuits Track Adaptor Nordic	CASAMBI + POT	22°	Warm White	PRI01841	PRI01843
40W	230Vac	3 Circuits Track Adaptor Nordic	CASAMBI + POT	22°	Neutral White	PRI01842	PRI01844
40W	230Vac	TIEBACK	Potentiometer	22°	Warm White	PRI01534	PRI01535
40W	230Vac	TIEBACK	Potentiometer	22°	Neutral White	PRI01536	PRI01537
40W	230Vac	TIEBACK	DALI	22°	Warm White	PRI01538	PRI01539
40W	230Vac	TIEBACK	DALI	22°	Neutral White	PRI01540	PRI01541
40W	230Vac	TIEBACK	PHASE	22°	Warm White	PRI01542	PRI01543
40W	230Vac	TIEBACK	PHASE	22°	Neutral White	PRI01544	PRI01545
40W	230Vac	TIEBACK	CASAMBI	22°	Warm White	PRI01546	PRI01547
40W	230Vac	TIEBACK	CASAMBI	22°	Neutral White	PRI01548	PRI01549
40W	230Vac	HOOK	Potentiometer	22°	Warm White	PRI01550	PRI01551
40W	230Vac	НООК	Potentiometer	22°	Neutral White	PRI01552	PRI01553
40W	230Vac	НООК	DALI	22°	Warm White	PRI01554	PRI01555
40W	230Vac	НООК	DALI	22°	Neutral White	PRI01556	PRI01557
40W	230Vac	ноок	PHASE	22°	Warm White	PRI01558	PRI01559
40W	230Vac	НООК	PHASE	22°	Neutral White	PRI01560	PRI01561
40W	230Vac	НООК	CASAMBI	22°	Warm White	PRI01562	PRI01563
40W	230Vac	НООК	CASAMBI	22°	Neutral White	PRI01564	PRI01565
40W	230Vac	WALL	Potentiometer	22°	Warm White	PRI01566	PRI01567
40W	230Vac	WALL	Potentiometer	22°	Neutral White	PRI01568	PRI01569
40W	230Vac	WALL	DALI	22°	Warm White	PRI01570	PRI01571
40W	230Vac	WALL	DALI	22°	Neutral White	PRI01572	PRI01573
40W	230Vac	WALL	PHASE	22°	Warm White	PRI01574	PRI01575
40W	230Vac	WALL	PHASE	22°	Neutral White	PRI01576	PRI01577
40W	230Vac	WALL	CASAMBI	22°	Warm White	PRI01578	PRI01579
40W	230Vac	WALL	CASAMBI	22°	Neutral White	PRI01580	PRI01581

<sup>\*\*</sup> Certifications : please check techical specifications







### **Items References**

Beam angle 40°

Power Consumption	Voltage	Mounting Versions	Dimming / Control	Beam Angle	Color Temperature	Black Finish	White Finish
40W	230Vac	3 Circuits Track Adaptor Nordic	Potentiometer	40°	Warm White	PRI01582	PRI01583
40W	230Vac	3 Circuits Track Adaptor Nordic	Potentiometer	40°	Neutral White	PRI01584	PRI01585
40W	230Vac	3 Circuits Track Adaptor Nordic DALI	DALI	40°	Warm White	PRI01586	PRI01587
40W	230Vac	3 Circuits Track Adaptor Nordic DALI	DALI	40°	Neutral White	PRI01588	PRI01589
40W	230Vac	3 Circuits Track Adaptor Nordic	PHASE	40°	Warm White	PRI01590	PRI01591
40W	230Vac	3 Circuits Track Adaptor Nordic	PHASE	40°	Neutral White	PRI01592	PRI01593
40W	230Vac	3 Circuits Track Adaptor Nordic	CASAMBI	40°	Warm White	PRI01594	PRI01595
40W	230Vac	3 Circuits Track Adaptor Nordic	CASAMBI	40°	Neutral White	PRI01596	PRI01597
40W	230Vac	3 Circuits Track Adaptor Nordic	CASAMBI + POT	40°	Warm White	PRI01845	PRI01847
40W	230Vac	3 Circuits Track Adaptor Nordic	CASAMBI + POT	40°	Neutral White	PRI01846	PRI01848
40W	230Vac	TIEBACK	Potentiometer	40°	Warm White	PRI01598	PRI01599
40W	230Vac	TIEBACK	Potentiometer	40°	Neutral White	PRI01600	PRI01601
40W	230Vac	TIEBACK	DALI	40°	Warm White	PRI01602	PRI01603
40W	230Vac	TIEBACK	DALI	40°	Neutral White	PRI01604	PRI01605
40W	230Vac	TIEBACK	PHASE	40°	Warm White	PRI01606	PRI01607
40W	230Vac	TIEBACK	PHASE	40°	Neutral White	PRI01608	PRI01609
40W	230Vac	TIEBACK	CASAMBI	40°	Warm White	PRI01610	PRI01611
40W	230Vac	TIEBACK	CASAMBI	40°	Neutral White	PRI01612	PRI01613
40W	230Vac	HOOK	Potentiometer	40°	Warm White	PRI01614	PRI01615
40W	230Vac	НООК	Potentiometer	40°	Neutral White	PRI01616	PRI01617
40W	230Vac	ноок	DALI	40°	Warm White	PRI01618	PRI01619
40W	230Vac	НООК	DALI	40°	Neutral White	PRI01620	PRI01621
40W	230Vac	ноок	PHASE	40°	Warm White	PRI01622	PRI01623
40W	230Vac	НООК	PHASE	40°	Neutral White	PRI01624	PRI01625
40W	230Vac	ноок	CASAMBI	40°	Warm White	PRI01626	PRI01627
40W	230Vac	HOOK	CASAMBI	40°	Neutral White	PRI01628	PRI01629
40W	230Vac	WALL	Potentiometer	40°	Warm White	PRI01630	PRI01631
40W	230Vac	WALL	Potentiometer	40°	Neutral White	PRI01632	PRI01633
40W	230Vac	WALL	DALI	40°	Warm White	PRI01634	PRI01635
40W	230Vac	WALL	DALI	40°	Neutral White	PRI01636	PRI01637
40W	230Vac	WALL	PHASE	40°	Warm White	PRI01638	PRI01639
40W	230Vac	WALL	PHASE	40°	Neutral White	PRI01640	PRI01641
40W	230Vac	WALL	CASAMBI	40°	Warm White	PRI01642	PRI01643
40W	230Vac	WALL	CASAMBI	40°	Neutral White	PRI01644	PRI01645

<sup>\*\*</sup> Certifications : please check techical specifications

#### **Accessories References**

	Black Finish	White Finish
22° Optical lens	ACC00189	ACC00220
40° Optical lens	ACC00222	ACC00223
Barn doors	ACC00225	ACC00226
Optical Zoom 18 < 42° with shutters	ACC00329	ACC00330



